

## WALL MOUNTS

### EP wall mount

The EP wall mounts are manufactured in multiple formats to suit the different installation techniques. They are specially interesting for the fixation of walls exceeding 3.5m height. The EP mounts should be installed 1.5 meters in height. Example: Wall of 4.5 metres, the EP mounts should be installed at 1.5 and 3.



# AKUSTIK+ AMC Mecanocaucho

## WALL MOUNTS

### EP wall mount

REF. AMC	SUMMARY	LOAD MÁX. (Kg.)	CODE
<b>E.P. 100</b> 	Mount designed for vibration damping of walls, equipped with long ring-attached screws for threading onto wooden or plastified walls. Maximum load per damper 10 kg.		24001
<b>E.P. 200</b> 	Mount designed for vibration damping of walls, equipped with flanges for fitting onto concrete. Maximum load per damper 10 kg.		24002
<b>E.P. 300</b> 	Mount designed for vibration damping of walls, equipped with flange and angle for fitting onto concrete and threaded. Maximum load per damper 10 kg.		24003
<b>E.P. 400</b> 	This mount is designed to be screwed to the profile, with the possibility of choosing different distances thanks to its 3 holes. The anchoring in to the wall is made by 2 fixing flanges.		24004
<b>E.P. 600</b> 	This mount is conceived to be fixed between two elements through two metal parts with "pre-drilled holes". The metal parts are easy to cut in order to adapt better to each work.		24008
<b>E.P. 650</b> 	This mount is conceived to be fixed between two elements through two metal parts with "pre-drilled holes". The metal parts are easy to cut in order to adapt better to each work. Following this idea we can realise a great amount of variants in order to adapt better to each work. Please enquire us if you need a more adapted system for your work.		24009
<b>E.P. 500</b> 	This mount is designed to offer an elastic base of the plasterboard plates.	<b>150</b>	23156